

ELITE SERIES DIRECT SHEAR

Automated Direct Shear Apparatus



HM-5765.3F



Scan to view more info online!

**Electromechanical-Actuated
Direct Shear Machine (Fully-Automated)
110/220VAC 50/60Hz**

ASTM: D3080; AASHTO: T236, BS:1377:7

The Humboldt HM-5765 Direct/Residual shear machine utilizes an electro-mechanical loading to apply vertical loads to the soil sample. Thereby eliminating the need for dead weights or an air supply used in other direct shear systems.

The HM-5765 is a microprocessor-based machine featuring a stepper-motor drive system and a 7" touch-screen display that allows the operator to control and monitor all test functions. Like all Humboldt Elite series machines, the HM-5765 is built with durable, high-quality components and features the use of a stepper motor, precision gears and gear box to ensure smooth and reliable operation, as well as precise results.

The HM-5765 is built around Humboldt's integral, 4-channel data logger with touch-screen control, which allows the HM-5765 to be used as a standalone device capable of full test control and data logging. It can also be controlled by a networked computer at any location with access to the network.

In stand-alone mode, the HM-5765 direct shear machine provides a 7" (178mm) touch-screen controller, giving you finger-tip control of your testing processes, as well as providing real-time, visual views of your data in both tabular and graphic formats. The waterproof, touch screen provides colorful, at-a-glance monitoring of testing functions without the use of a computer. Oper-

ators can see all the data in several formats at the machine while the test is running. Data can then be viewed simultaneously or downloaded later to a computer in the lab, in the next room or at a different location, while also providing report generation capabilities from within Humboldt's NEXT software or our enhanced HM-5700SW Direct Shear Reporting Software.

When operated from a networked computer the NEXT software provides robust machine and test control, and report generation. It also provides the ability to control and monitor multiple machines from a single computer.

The HM-5765 comes with two 2,000 lbf (10kN) capacity load cells, a single 1" (25.4mm) horizontal strain transducer, and a single 0.4" (10.2mm) vertical strain transducer. Humboldt's HM-5700SW NEXT Direct Shear testing software is also included with the purchase. **Shear box assemblies and related accessories are not included and should be ordered separately.**

Humboldt's exclusive, counter-balance device for ASTM D3080 compliance is included with the HM-5765.

**Electromechanical-Actuated Direct Shear Machine
(Fully-Automated) 110/220VAC 50/60Hz HM-5765.3F**

Shipping wt. 168 lb (76kg)

HM-5765.3F Specifications:	
Horiz. movement	1" (25mm) Maximum
Horiz. shear force	2000 lbf (10kN)
Vertical load	2000 lbf (10kN)
Data Channels	4
Speed Range	0.00001 to 0.49999 in./min. 0.00001 to 12.9999 mm/min.
Dimensions (L x D x H)	30" x 15.5" x 22" (760 x 394 x 558mm)
Voltage	110/220V 50/60Hz - 6.5amps
Electro-Mechanical Direct Shear System Requirements	
AC Supply	110/220 VAC 50/60 Hz 5 Amp

 **UPGRADE**
Counter-balance device for ASTM D3080 compliance. Not available anywhere else. Also available as a retrofit kit. HM-2560A.1.



Controller Specifications:	
Display (Resistive Touch)	7" (178mm) VGA (480 x 800)
Real-time test data	Graphic and tabulation
Processor	Dual 32-bit ARM
RAM	64MB
Memory, non-volatile	4GB
Analog to digital converter	24 bit
Data acquisition	4 Channels
Logging Rate	effective rate of 320 readings per second
Multi-test storage	1000
Points per test	3000
USB port (front)	export data, import/export calibration data
USB port (back)	provides external power for wireless access point
Ethernet connection	for network connectivity
24-bit differential analog to digital converter	4
Ambient temperature sensor	1
Firmware Update	Flash drive

Computer Control

NEXT software and the enhanced Direct Shear module, HM-5700SW, is included with the HM-5765 direct-shear machines. This software provides robust machine control, data acquisition and report generation for those using a computer to control direct shear testing operations.

In addition, operators have the ability to view and control testing operations from a PC in the lab, in the next room or at a different location, while also providing report generating capabilities using the direct shear test-specific software module.

So, whether you are controlling a single direct-shear machine, controlling multiple machines or even a complete geotechnical lab, Humboldt's NEXT software, in conjunction with Humboldt's HM-5765 Direct-shear machines, provides a complete solution for acquisition, recording and presentation of direct-shear testing data in tabular and graphic chart formats.

- Machine control, and data acquisition via a networked computer
- Provides the ability to use Humboldt's Next Software's, advanced test-specific modules
- Real-time graphical chart and numerical display of tests via computer display
- Effective sampling rate of 320 readings per second
- Stores 1000 tests with up to 3000 points per test



Typical Test Setup for HM-5760 & HM-5765

Description	Part #
Fully-Automatic Direct Shear (includes (2) 2,000 lbf (10kN) capacity load cells; 1" (25.4mm) horizontal strain transducer, and a 0.4" (10.2mm) vertical strain transducer)	HM-5760.3F (Pneumatic) or HM-5765.3F (Electro-Mechanical))
NEXT Direct Shear software module (included with HM-5760 and HM-5765)	HM-5700SW
Shear box assembly (specify size)	HM-2751.XX(S/D)
Shear box cutter (specify size)	HM-2702.XX(S/D)
Dolly/tamper (specify size)	HM-2703.XX(S/D)
* XX Requires a sample size designation, see page 4.24 for choices	
Additional Items Required	
PC computer	not supplied
Direct Shear/Consolidation Installation Kit	HM-4168
Desiccant Dryer, Silica Gel	HM-4222
Filter/Regulator	HM-4223



- Up to 255 individual tests can be run simultaneously from a single PC
- Provides advanced graphing capabilities
- Provides full-unit customization
- Reports can also be exported to an Excel or CSV file, if desired, and, we can provide custom integration/export solutions for LIMS, EQiS, gINT, etc.

Shear Box Assemblies for HM-5765, HM-5760, HM-5755, HM-5750		
Size	Square	Round
2.0"	HM-2751.20S	HM-2751.20D
2.42"	HM-2751.24S	HM-2751.24D
2.5"	HM-2751.25S	HM-2751.25D
4.0"	HM-2751.40S	HM-2751.40D
50mm	HM-2751.50S	HM-2751.50D
60mm	HM-2751.60S	HM-2751.60D
100mm	HM-2751.100S	HM-2751.100D



NOTES

Shearbox assemblies include: sample box, (2) porous plates, (1) loading pad, and (1) grid plate. All shearboxes feature mounting screws for use with the HM-2750 ASTM D3080-compliant counter-balance device.



HM-2703.25S



HM-2703.25D



HM-2702.S



HM-2755.25S



HM-2704.25S



HM-2702.25D



HM-1220.25.4



HM-2704.25D

Dolly Tamper		
Size	Square	Round
2"	HM-2703.20S	HM-2703.20D
2.42"	HM-2703.24S	HM-2703.24D
2.5"	HM-2703.25S	HM-2703.25D
4.0"	HM-2703.40S	HM-2703.40D
50mm	HM-2703.50S	HM-2703.50D
60mm	HM-2703.60S	HM-2703.60D
100mm	HM-2703.100S	HM-2703.100D

Cutter		
Size	Square	Round
2"	HM-2702.20S	HM-2702.20D
2.42"	HM-2702.24S	HM-2702.24D
2.5"	HM-2702.25S	HM-2702.25D
4.0"	HM-2702.40S	HM-2702.40D
50mm	HM-2702.50S	HM-2702.50D
60mm	HM-2702.60S	HM-2702.60D
100mm	HM-2702.100S	HM-2702.100D

Calibration Disk		
Size	Square	Round
2"	HM-2755.20S	HM-1220.20.4
2.42"	HM-2755.24S	HM-1220.24.4
2.5"	HM-2755.25S	HM-1220.25.4
4.0"	HM-2755.40S	HM-1220.40.4
50mm	HM-2755.50S	HM-1220.50.4
60mm	HM-2755.60S	HM-1220.60.4
100mm	HM-2755.100S	HM-1220.100.4

Porous Plate		
Size	Square	Round
2"	HM-2704.20S	HM-2704.20D
2.42"	HM-2704.24S	HM-2704.24D
2.5"	HM-2704.25S	HM-2704.25D
4.0"	HM-2704.40S	HM-2704.40D
50mm	HM-2704.50S	HM-2704.50D
60mm	HM-2704.60S	HM-2704.60D
100mm	HM-2704.100S	HM-2704.100D



HM-001076



HM-003274



HM-003275A

Installation and Spare Parts Kit HM-4168
 Direct Shear Installation and Spare Parts Kit provides tubing, fasteners and tools to complete an installation of pneumatic direct shear equipment.
Installation and Spare Parts Kit HM-4168
 5 lb (2.3kg)



HM-4168

Accessory	Model
Replacement Pressure Ball 5/8" 440 Stainless Steel	HM-001076
Screw, Black Head	HM-003274
Screw, Red Head*	HM-003275A

*Red Head Screws are used to hold the shear box together and are made with plastic heads, which will shear off before shear box can be damaged.



Humboldt Mfg. Co.
 www.humboldtmfg.com
 875 Tollgate Road
 Elgin, Illinois 60123 U.S.A.

U.S.A. Toll Free: 1.800.544.7220
 Voice: 1.708.456.6300
 Fax: 1.708.456.0137
 email: hmc@humboldtmfg.com